

2 - Core

Nominal Size	Min. Insulation Thickness	Armour Wire Diameter	Min. Sheath Thickness	Nominal Overall Diameter	Approx. Weight
(mm ²)	(mm)	(mm)	(mm)	(mm)	(kg / km)
2 x 1.5	0.7	0.9	1.8	12.3	305
2 x 2.5	0.7	0.9	1.8	13.6	354
2 x 4	0.7	0.9	1.8	14.7	416
2 x 6	0.7	0.9	1.8	15.9	507
2 x 10	0.7	0.9	1.8	18.0	647
2 x 16	0.7	1.3	1.8	20.0	993
2 x 25	0.9	1.3	1.8	20.4	1290
2 x 35	0.9	1.6	1.9	23.4	1500
2 x 50	1.0	1.6	2.0	25.8	1890
2 x 70	1.1	1.6	2.2	29.0	2450
2 x 95	1.1	2.0	2.3	33.1	3300
2 x 120	1.2	2.0	2.5	36.1	4020

3 - Core

Nominal Size	Min. Insulation Thickness	Armour Wire Diameter	Min. Sheath Thickness	Nominal Overall Diameter	Approx. Weight
(mm ²)	(mm)	(mm)	(mm)	(mm)	(kg / km)
3 x 1.5	0.7	0.9	1.8	12.8	335
3 x 2.5	0.7	0.9	1.8	14.1	388
3 x 4	0.7	0.9	1.8	15.3	471
3 x 6	0.7	0.9	1.8	16.6	576
3 x 10	0.7	0.9	1.8	19.5	884
3 x 16	0.7	1.3	1.8	21.2	1159
3 x 25	0.9	1.3	1.8	25.5	1800
3 x 35	0.9	1.6	1.9	28.0	2230
3 x 50	1.0	1.6	2.0	28.5	2490
3 x 70	1.1	1.6	2.2	32.2	3290
3 x 95	1.1	2.0	2.3	37.0	4440
3 x 120	1.2	2.0	2.5	40.4	5470
3 x 150	1.4	2.5	2.5	45.5	6930
3 x 185	1.6	2.5	2.7	49.8	8350
3 x 240	1.7	2.5	2.9	55.1	10400
3 x 300	1.8	2.5	3.0	60.2	12600
3 x 400	2.0	2.5	3.0	66.6	14600