

6387-1Cun-FR

No. of Cores & Nominal Size	Min. Insulation Thickness	Armour Wire Diameter	Nominal Overall Diameter	Max. Conductor DC Resistance at 20°C	Approx. Weight
(mm ²)	(mm)	(mm)	(mm)	(Ω / km)	(kg / km)
1.5	0.7	1.4	6.9	12.1	39
2.5	0.7	1.4	7.4	7.41	58
4	0.7	1.4	7.9	4.61	84
6	0.7	1.4	8.4	3.08	105
10	0.7	1.4	9.4	1.83	166
16	0.7	1.4	10.9	1.15	238
25	0.9	1.4	12.4	0.727	450
35	0.9	1.4	13.5	0.524	550
50	1.0	1.4	15.7	0.387	730
70	1.1	1.4	17.8	0.268	951
95	1.1	1.5	20.0	0.193	1302
120	1.2	1.5	21.8	0.153	1615
150	1.4	1.6	24.1	0.124	2014
185	1.6	1.6	26.6	0.0991	2495
240	1.7	1.7	29.6	0.0754	3160
300	1.8	1.8	32.6	0.0601	3901
400	2.0	1.9	36.3	0.047	4990
500	2.2	2.0	40.5	0.0366	6170
630	2.4	2.2	45.5	0.0283	6860
800	2.6	2.3	50.6	0.0221	8335
1000	2.8	2.4	56.0	0.0176	10415